



HIGH SENSITIVITY FORMALDEHYDE GAS MONITOR

Gas Detection For Life

FP-330 Model



Features

- Small and compact
- Highly sensitive and ideal for low level formaldehyde concentrations
- Interference-free detection
- Easy detection tape replacement with plug in cassette
- Tape remainder display and tape end warning alarm provided
- PPM digital display
- Easily transportable
- 115 VAC powered
- Alarm relays
- 4-20mA output

Applications

- Furniture and woodworking
- Coating and varnishing
- Engineered wood products
- Medical / veterinary
- Painting & corrosion resistant finishes
- Carpet manufacture & storage
- Adhesives
- Heat treatment operations
- Manufactured homes/trailer/RV inspection

RKI's paper tape monitors utilize highly sensitive colorimetric tapes to achieve interference free gas detection. The FP-330 is equipped with an easily replaceable tape that is highly specific to Formaldehyde. This model is equipped with a digital display showing the type of gas and concentration in PPM. The FP-330 will also display remaining tape life as well as an end of tape alarm.

The FP-330 has audible and visual alarms, as well as alarm relay contacts and 4-20mA output. A unique "Tape Saver mode" extends tape life in applications where high background gas levels may be present.

The FP-330 meets and exceeds OSHA and NIOSH compliance requirements, and does not respond to interfering gases (hydrocarbons, alcohols, solvents, CO, etc.) that may be present in industrial/manufacturing environments.

FP-330 Model

Model	FP-330 HCHO 0 - 0.500 ppm	FP-330 HCHO 0 - 1.00 ppm
Detection principle	Photoelectric photometry method using tape cassette	
Detection tape	Plug in cassette, FCL-018	
Detection gas	Formaldehyde (HCHO)	
Detection range	0.030 to 0.500 ppm	0.05 to 1.00 ppm
Zero suppression	0.030 ppm	0.05 ppm
Measuring cycle	1800 seconds (30 minutes)	600 seconds (10 minutes)
Resolution	0.005ppm	0.01 ppm
Flow rate	450ml/min.	
Max. tubing length	2m	
Accuracy	+/-20% of indication value + 1 digit	
Tape operation time	1 month with no alarm conditions. (see note below*)	
Alarm Indication	Warning and alarm with audible and visual indications	
Alarm point	Two alarms 1st 0.080ppm, 2nd 0.300ppm	
Alarm operation	Latching alarm (standard) or non-latching (option) Lamp : Caution = Yellow, Alarm = Red, with buzzer	
Self-diagnosis	Low flow, tape cut, sensor failure, etc.	
External output signal	4-20mA (load resistance: below 300 Ω)	
Operating temperature & humidity	5~35°C 20~60% RH (non condensing)	
Gas inlet/outlet	OD 6mm with fittings	
Power supply & power	100VAC to 220VAC universal power, +/-10%	
Dimensions & weight	Approx. 6.5(W) x 7.8(H) x 10.4(D) Approx. 12.125lb 164 (W) x 198 (H) x 263 (D) mm, 6.5kg approx.	

Tape Saver mode is available for above all three ranges;

0H: Normal operation.

1H: One measurement during one hour.

2H: One measurement during two hours.

*When HCHO exists in the background continuously over 0.03 ppm, the tape on FP-330 advances after every measurement, so the tape is consumed very quickly. In this case, to save the tape, the Tape Saver mode is provided on the FP-330.

Note: Using Tape Saver mode 2H or Normal operation (with existing background continuously below 0.03 ppm)

*with tape remaining indication (count down from 7days)

*with tape end alarm

Specifications subject to change without notice.



A9812



ISO 9001:2000

Toll Free: (800) 754-5165 • Phone: (510) 441-5656

Fax: (510) 441-5650 • www.rkiinstruments.com

Authorized Distributor: